

Specifications

Model	FS1006PL		
Power	Power supply	External Power Adaptor	
	Voltage Range	DC48~57V	
	Switch Consumption	<5W	
Ethernet	Speed	1~5 Port : 10/100Mbps, Uplink:100Mbps	
	Transmission Distanc	1-4port 100Meters with 100Mbps 200Meters with 10Mbps Uplink:100Meter with 100Mbps	
Network Switch	Ethernet Standard	IEEE 802.3/802.3u/802.3af/802.3at	
	Switching capacity	1.2G	
	Transfer Rate	14,880pps for 10Mbps 14,880pps for 100Mbps	
	MAC Address	1K MAC address table	
Function	On	—	The vlan and 200meters is start to work
Link/ACT	On	Green	The port is connecting
	Blinks	—	The port is receiving or transmitting data
	Off	—	The port is not linked successfully with the device
POE	On	Orange	PD is connected
	Off	—	No PD is connected or power forw arding fails
	Capacity		55W
Bandwidth	PoE pin assignmnet	V+(RJ45 Pin 1,2), V-(RJ45 Pin 3,6)	
Environment	Working Temperature	0~40°C	
	Storage Temperature	-40~70°C	
	Humidity Non condensing	0~85%	
Mechanical	Dimension	102mm×75x22mm	
	Color	Gray	