

DIGITUS QSFP+ 40 Gbps Module, Multimode, 850nm, 100m

DN-81300

EAN 4016032424246



QSFP 40 Gbps Module, Multimode, 850nm, 100m MPO Connector, OM3

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- QSFP+ module
- Compatible with the following manufacturers: Ubiquiti, Allied Telesis, Allnet, CISCO, D-Link, Edimax, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE, Avaya, Mikrotik, ENTERASYS, FINISAR, FORCE 10, RIVERSTONE, Fortinet
- Connector: 1x MPO
- Wavelength: 850nm, Multimode
- 40 Gbps Maximum Data Rate
- Transmission power: minimum -7.6 dBm, maximum 2.4 dBm
- Sensitivity Receiving Power: Minimum -9.5 dBm
- For a Distance of up to 100m (OM3) and 150m (OM4)

- Safe fast-locking mechanism
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- Compliant to IEEE 802.3ba 40 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- 3.3V power supply
- Suitable for OM3/OM4 multimode fiber cables
- Operating temperature: 0 °C ~ 70 °C
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Connector: MPO
- DDM Support: yes
- Distance (km): 0.1
- Mode: Multimode
- Ethernet speed: 40 Gigabit
- Wavelength: 850 nm

Package contents

- QSFP+ module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	1,080.00	55.00	39.50	25.50	55,399.00
Packaging Unit Inside	1	9.00	12.00	9.50	3.50	399.00
Packaging Unit Single	1	9.00	12.00	9.50	3.50	399.00
Net single without Packaging	1	0.04	12.00	2.00	1.10	0.00

More images:

