

DIGITUS 24 Port FE PoE Switch 2 Uplink Ports (SFP / RJ45)

DN-95356
EAN 4016032485049



24 Port 10/100 Mbps PoE 24x10/100Mbps PoE RJ45 Ports, 1 xGE RJ45, 1xSFP

"DN-95356 PoE Switch is 24-port 10/100Mbps PoE + 1G Combo +1GE PoE Switch. The PoE ports can automatically detect and supply power to IEEE802.3af/at compliant Powered Devices (PD). The electrical power and data transmission on the same cable can expand your network to the places where no power lines or outlets, where you can install devices such as APs, IP cameras, or IP phones etc. The PoE Switch provides a simple, cost-effective, and non-blocking wire-speed performance with 11-inch metal shape for rack deployment in office or department network application."

Key Function: VLAN & CCTV

- 24*10/100Mbps PoE RJ45 Ports
- 1*10/100/1000Mbps Combo Ports
- 1*10/100/1000Mbps RJ45 Ports
- Complies with IEEE802.3af/at Power over Ethernet
- Supports PoE Power up to 32W for each PoE port
- Auto detect power device
- Remote power and Data feeding up to 100m
- Flow Control for Full Duplex operation and back pressure for Half Duplex Operation
- Support VLAN and CCTV function
- 16K MAC address, automatic address learning and address aging
- Support Energy-Efficient Ethernet (EEE) function IEEE802.3az

- Support PD Alive function the switch port is disconnected will automatically connected
- Standard: IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at
- Interface: 24*10/100Mbps RJ45 port, 1*10/100/1000Mbps Combo port 1 * 10/100/1000Mbps RJ45 port
- Network media: 10BASE-T: UTP cables in categories 3, 4, 5 (≤100m), 100BASE-TX: UTP cables in categories 5, 5e (≤100m), 1000BASE-T: UTP cables in categories 5e, 6 (≤100m), 1000BASE-X: SMF, MMF
- LED: PWR, PoE, LINK/ACT, PoE Max
- Key function: VLAN & CCTV
- MAC address table: 16K, auto-learning, auto-aging
- Transmission mode: Store and forward
- Maximum packet length: 16K
- Switching capacity: 8.8G
- Packet forwarding rate: 6.5 Mpps
- Packet buffer: 4M bit
- Dimensions (L*W*G): 280*180*44mm
- Industrial usage: no

Package contents

- 24 +2 Port FE PoE Switch
- Connection Cable
- Connection Cable
- QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	5	12.38	26.00	38.30	42.60	42,421.10
Packaging Unit Inside	1	2.48	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.48	8.00	23.00	37.00	6,808.00
Net single without Packaging	1	1.85	4.40	18.00	28.00	2,217.60

More images:

