

DIGITUS mini GBIC (SFP) Module, 10Gbps, 0.3km, with DDM Feature

DN-81200

EAN 4016032324133



10G SFP+ Module, Multimode, DDM LC Duplex Connector, 850nm, up to 300m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, CISCO, D-Link, Edimax, Hirschmann, Intellinet, KTI Networks, Level One, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation

- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm
- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangssensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Connector: LC
- DDM Support: yes
- Distance (km): 0.3
- Mode: Multimode
- Ethernet speed: 10 Gigabit
- Wavelength: 850 nm

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.04	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

SFP Modules							
Product Number	SKU Code	Speed Port Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version
10G SFPs							
29A-100	29A-100-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-100	29A-100-010-01	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
SFP+							
29A-1000	29A-1000-010	10 Gbps	330 m	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1000	29A-1000-010-01	10 Gbps	330 m	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1000	29A-1000-010-02	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1000	29A-1000-010-03	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1000	29A-1000-010-04	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
10G							
29A-1000	29A-1000-010-05	10 Gbps	300 m	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1000	29A-1000-010-06	10 Gbps	300 m	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
Fast Ethernet							
29A-1111	29A-1111-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1114	29A-1114-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1115	29A-1115-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1001	29A-1001-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1002	29A-1002-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1003	29A-1003-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1004	29A-1004-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓
29A-1005	29A-1005-010	10 Gbps	27 km	LC Duplex SFP+	74.7 nm CW/1310 nm	-40 to 70 °C	✓

