

DIGITUS mini GBIC (SFP) Module, 1.25 Gbps, 0.55km

DN-81000

EAN 4016032305651



1.25 Gbps SFP Module, Multimode LC Duplex Connector, 850nm, Up to 550m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Ubiquiti, Allied Telesis, Allnet, CISCO, D-Link, Edimax, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE, Avaya, Mikrotik, ENTERASYS, FINISAR, FORCE 10, RIVERSTONE, Fortinet
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Duplex
- 1000Base-SX - For Short Haul
- Wavelength: 850nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- For a Distance of up to 0.55km
- Suitable for 50/125µm and 62.5/125µm multimode fiber cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Connector: LC
- DDM Support: no
- Distance (km): 0.5
- Mode: Multimode
- Ethernet speed: Gigabit
- Wavelength: 850 nm

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	3.10	11.80	9.30	340.19
Net single without Packaging	1	0.02	1.00	5.90	0.80	0.00

More images:

SFP Modules						
Product Number	Data Code	Speed	Distance	Connector	Wavelength	Operating Temperature
250-0101	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0102	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0103	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0104	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0105	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0106	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0107	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0108	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0109	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0110	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0111	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0112	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0113	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0114	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0115	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0116	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0117	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0118	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0119	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0120	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0121	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0122	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0123	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0124	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0125	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0126	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0127	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0128	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0129	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0130	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0131	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0132	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0133	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0134	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0135	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0136	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0137	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0138	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0139	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0140	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0141	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0142	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0143	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0144	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0145	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0146	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0147	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0148	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C
250-0149	4010000000000	100 Mbit/s	10 km	LC Duplex	1310 nm	-20 to 70 °C
250-0150	4010000000000	100 Mbit/s	10 km	LC Duplex	1550 nm	-20 to 70 °C

